

PureVista 12.5, 25, 50 & 100-gram Activation Instructions

v4.0 _ September 14, 2020

Equipment:	
Scissors/Utility Knife	Used to cut open safety seal on PureVista package.
Bottle or small jug for water used to activate PureVista	Bottle is used to fill canisters and activate PureVista using the specified amount of water listed on the canister label.
Tape & polyethylene plastic (non-residue duct tape ideal)	To seal seams and hinges on man-doors, and for sealing with plastic of larger areas & vents to prevent gas from escaping to outside of building and/or areas that will not be treated.

Pre Treatment:	
Clean prior to treatment	Ensure all treatment areas and surfaces are clean and free of organic matter. Dirt and other organic buildups can keep ClO ₂ gas from effectively contacting the surface. (eg. Food, heavy grease, dirt or dust, etc). Contact PureLine with any questions about other materials or chemicals that will be in the treatment area, for which you have questions or concerns about possible interactivity between the chlorine dioxide and said materials.
Signage	Use appropriate DO NOT ENTER signage across entry ways to treatment area(s) to notify all persons that the area is being treated with ClO ₂ gas.
Exhaust Planning to remove residual gas at completion of treatment	Plan how you will exhaust the residual gas upon cessation of chlorine dioxide treatment. For small areas (cars, planes, homes etc) this is nothing more than opening a door. For large areas (Food processing plants), exhaust system (whether HVAC or fans) should be turned on from outside the treatment area, and exhausted to outside of building. Exhaust through the roof is ideal. Any gas released will quickly dissipate in the atmosphere.
Sealing confirmation	Inspect sealing of all doors, entry ways and vents to assure all areas are sufficiently sealed to prevent gas from escaping to the outside of treatment area and/or escaping beyond the areas that are being treated. Most man doors have appropriate weather seals that require no extra sealing. If you believe a man door will leak, then use non-residue duct tape or common painter's tape around the seams of doors and including the hinges of the doors. Vents and open entry ways should be sealed with polyethylene plastic (of any thickness), and securely sealed with tape on sides, tops, and bottoms. UV light will break down chlorine dioxide, therefore; cover windows and shut off lights to improve efficacy. Cars, Planes, homes generally require little if any sealing.

Treatment:	
Decontamination capability	<ul style="list-style-type: none"> - For microbial growth, use 100 grams per 500 cubic feet. - As a virucide, use 100 grams per 4,000 cubic feet. - For odor control, use 100 grams per 1,000 square feet.
Agitation of PureVista canister before opening	IMPORTANT: Shake canister vigorously for 3 – 5 seconds to loosen PureVista powder and assure proper activation of chemical.
PureVista Canister Placement	Place PureVista canisters equidistantly from each other in the areas that are being treated. To avoid bleaching risk, do not place directly on carpet, leather or textile surfaces.
Activation	IMPORTANT: Remove lid and place lid upside down on a hard surface. Remove disposable fill cup from canister and fill cup with water to specified level. Pour water into PureVista canister and agitate lightly to mix water and chemical powder. Place face-up and inside the upside-down lid. Repeat for additionally deployed canisters. Note: room temperature tap water is recommended.
Final Sealing	Close all doors and provide final sealing upon exiting treatment area.

continued on next page

PureVista 12.5, 25, 50 & 100-gram Activation Instructions

v4.0 _ September 14, 2020

Post Treatment:	
Personal Protection Equipment (PPE)	For treatments consisting of more than the equivalent of ten (10) PureVista 100's (1000 grams), it is recommended to have a full-face respirator & filters rated for ClO ₂ , nitrile or latex gloves, safety glasses, and a personal ClO ₂ monitor. For smaller applications such as cars, planes, etc, nitrile gloves and safety glasses are recommended in observance of safe chemical handling practices.
Exhaust residual ClO ₂ gas	For large treatment plans and after treatment time, turn on exhaust system from outside treatment area. Exhaust system (whether HVAC or fans) should be turned on from outside the treatment area, and exhausted to outside of building. Exhaust through the roof is ideal. If exhaust through doorway(s) leading to outside is required, set up a perimeter of approximately 50 feet to prevent accidental exposure to chlorine dioxide. The gas will quickly dissipate in the atmosphere. For smaller areas, including, car, planes, small rooms, etc, simply open the door and allow gas to naturally escape. In cars and planes this generally only takes a few minutes.
Removal of Signage	Remove ONLY after the OSHA 8-hour safe gas level of 0.1 ppm or less has been reached.
De-activation of PureVista after completion of treatment.	Complete neutralization of PureVista is optional. If PureVista neutralizer is used, pour the neutralizer into each canister. 100 ml for PureVista 100, 50 ml for PureVista 50, etc. Replace lid on canister and shake gently for 3 – 5 seconds and discard the closed canister in regular trash container. Solution is now a salt solution and harmless to the environment.

Personal Protection Equipment (PPE):	
Rubber Gloves (nitrile or latex)	As with any chemical mixture, do not touch PureVista powder with bare hands. Rubber gloves are recommended.
Safety Glasses	Always wear safety glasses when using or handling PureVista.
Chlorine Dioxide (ClO ₂) Monitor	Large Treatment plans only - A personal chlorine dioxide monitor may be worn near the collar of the shirt for measuring residual gas levels. See the following link for the recommended equipment: Honeywell BW Solo
Full-Face Respirator & filters rated for ClO ₂	Large Treatment plans only Full-Face respirator should be worn anytime you are deploying more than 1,000 grams of PureVista. See the following links for the recommended equipment: Full face respirator
Personnel Readiness & Safety	Large Treatment plans only When deploying more than 1000 grams of PureVista, two persons should work together for safety purposes.

See PureVista Material Safety Data Sheet or www.purevista.info for More Information